## ROSTRA ACCESSORIES INC. 3056 NC HWY 5 ABERDEEN NC. 28315 800-782-3379

All instructions, warranties and other collateral documents are subject to change at the sole discretion of Rostra Accesories, Inc. For the latest available information or product literature, visit www.rostra.com and click on the support tab.

WWW.ROSTRA.COM
ALL RIGHTS RESERVED 7/30/2018





BEFORE INSTALLATION PLEASE READ THIS MANUAL, AFTER INSTALLATION LEAVE WITH THE VEHICLE FOR THE END USER.

## Controls & Features

- 1: Removable Sun Shade
- 2: Locking Screws
- 3: U-Bracket
- 4: 9" LCD Panel
- 5: MENU Button
- 6: CH1 / Left Select Button
- 7: CH2 / Right Select Button
- 8: Power On/Off Button
- 9: CH3 / Down Select Button
- 10: CH4 / UP Select Button
- 11: Mode Button Selects View Mode

To remove the sun shade carefully press up at the bottom of both sides. The Screen will release, then carefully lift away from the LCD panel. DO NOT force the shade or put pressure on the panel.

5678 9101112

# Wiring Connections



Specifications		
Screen size	9 inch	
Aspect ratio	16:9	
Luminance	250cd/ m²	
Resolution	800*RGB*480	
Audio & Video	1 Audio Input, 4 Video Inputs, 4 Seperate Triggers	
System	Switches Between PAL & NTSC Automatically	
Voltage	12 V - 24 V	
Language	English, Deutsch, Francais, Espanol, Portugais, Italiano, Chinese, Turkish	
OSD Menu	Selects Picture, Volume, Mirror Image, Language, Delay,	
Built-in speaker	1 Channel Audio On Input #1	
Bracket accessories	U Type Bracket Included	
Sunshade	Included, Removable	
Mode	Full Screen, 2 Split, 3 Split, 4 Split	
Set up	Mirror Image Selectable & Adjustable Image Delay After Trigger On All Inputs	

## Menu Options

- Press the MENU button to enter the OSD.
- Press MENU again to move to the next Option Screen.
- Use the UP/Down Arrow buttons to select a option.
- Use the Right/Left Arrow buttons to increase or decrease the selected option.

Picture:

Bright, Contrast, Color, Tint, Reset.

Volume:

Adjusts the Volume from Camera 1

Mirror:

Select Normal or Mirror image on this camera.

System:

Changes the OSD Menu Language


Clock:

Set Camera View Delay after trigger is off. Select from 0 - 10 Seconds delay for each camera input.


#### **Monitor Stand Installation**

1: Remove the U-Bracket from the Monitor. Find a location that is desired for proper viewing. Before mounting the bracket insure the Monitor doe not block any safety device or the drivers view.






2: Mount the U-Bracket securely uing self tapping screws or nuts and bolts (not provided).






3: Re-attach the monitor to the bracket and adjust to a desired viewing angle. Tighten the thumb screws to insure the monitor is secure





## Monitor Installation - Optional Mount 250-8132 Not Included


1: Find a location for the mount, Rostra does not recommend using mounts with double sided tape on 9" monitors. The Monitor may come loose and be a hazard or get damaged. If using this type of mount, use screws to securely attach the base.




Self tapping Screws or nuts and bolts are recommended


2: Slide the T-Bolt into the slot in the rear of the monitor. Do Not use the u-bracket when using a slid mount.








4: Turn the thumb screw clockwise to tighten into place at the desired height.



5: Adjust to the desired viewing angle and tighten the base thumb screw to secure.



### **Contents**

1. Monitor	2.User manual*1PCS		
	COLOR ADMINISTRATION OF THE PROPERTY OF THE PR		
3.Power cable 1 PCS			
4.Sunshade*1 PCS	5.Bracket accessories*1 PCS		

#### WARNINGS:

ROSTRA ACCESSORIES IS NOT RESPONSIBLE FOR IMPROPER INSTALLATION, DAMAGE TO THE VEHICLE, OR ACCIDENTS DUE TO IMPROPER USE. CAMERA SYSTEMS ARE ONE OF MANY SAFETY FEATURES AND THE DRIVER HAS THE RESPONSIBILITY TO ALWAYS INSURE SAFE OPERATION OF THE VEHICLE.

ALWAYS CONSULT A PROFESSIONAL INSTALLATION TECHNICIAN TO INSURE THE INSTALLATION MEETS ALL LOCAL AND FEDERAL LAWS . SEE WWW.ROSTRA.COM FOR WARRANTY INFORMATION.