

Technical Tip: Rostra 250-2951

Programming Timer Mode:

1. With the vehicle's engine powered on, hold the Push Button for > 10 seconds. Release the push button when the LED starts to flash. The LED will blink in a 9-flash sequence. Each LED flash represents a 1-minute interval for selection.
2. Select the power-off delay value by pressing and holding the push button after the desired number of flashes. (Example: 6 minutes = 6 flashes).
3. Continue holding the Push Button until it repeats the sequence you chose, then release.
4. Press and hold the Push Button immediately until you see two flashes. Release to save the single digit power-off delay time.
5. If you want to add more time, continue to hold the Push Button after the two flashes. Once the fast LED blinking sequence begins, release the Push Button. The selected time will now have 10X more time. (Example: You chose 5 on the first sequence, you will now have 50 minutes). Power-off delay has been saved.

Power Mode (Unit Turns Off with Engine):

1. Start with the vehicle's engine OFF and confirm the LED is not flashing.
2. Press and hold the Push Button and power on the engine to power on the SourcePWR+ unit.
3. The SourcePWR+ unit's LED will begin a 20-flash sequence.
4. Once the SourcePWR+ unit stops blinking and LED remains on, release Push Button. The SourcePWR+ unit is now in *Power Mode*.
5. To return to *Timer Mode*, repeat these steps.

